



TRANSTRONIC®

R

INKLINATOR® CMI Bench



Inclination=?°
Side=?°
Length=?

**Total instrument system for all types of benching drilling rigs.
The system is built in modules that can be selected depending
of the specific requirements. If any other modules are wanted
later it is convenient to connect later to the system.**

The modules

- Angle measurement vertical
- Angle measurement and penetration rate
- Swinging cab
- Length measurement from laser plane
- Length stop
- GPS compass



TRANSTRONIC®

Inklinator CMI Bench is built on the latest CAN Open technolog. This makes the system very easy to mount, calibrate and zero-set.

All sensors and cables are manufactured to survive the harsch environment on a drill rig.

The angle transducer is mounted on the feeder and is has no moving parts. The display shows the anlges in the direddction of the sight. When drilling, the display shows penetration rate and hole length.

The system is also equipped with a diagnostic program which makes it possible to check transducers and cables from the indicator without any tools or instruments.



Specification:

		Standard	Optional
Measurement range std.	side angle	+/- 60 deg	+/- 180 deg
	inclination angle	+/- 60 deg	+/- 180 deg
Accuracy, all transducers better than, 0,2 deg			
Hole length measurement range, 0 – 99,9 m			
Hole length measurement accuracy, +/- 1%, minimum 0,05 m			
Penetration rate measurement range, 0 – 9,99 m/min			
Power supply, 10 – 30 VDC, 0,3 A			
Enclosure, IP65, Splash proof			
Working temperature, -20 - +50 deg Celcius			



TRANSTRONIC®